

RECEIVED
CENTRAL FAX CENTER
SEP 06 2006

IN THE CLAIMS:

1. (Currently Amended) A breathing circuit component or conduit connector for
interconnection with a breathing assistance apparatus and having an interior for conveying

5 respiratory gas comprising:

a sensor entry port extending perpendicularly from said conduit connector and configured
to receive a sensor, and

a locating depression notch provided in a wall of said sensor entry port configured to
receive a complementary locating tooth from a sensor, the interconnection of said depression
10 notch and a tooth providing a predetermined orientation of a sensor within said interior.

2. (Currently Amended) A breathing circuit conduit connector component as claimed in
claim 1 further comprising a sensor for locating within said sensor entry port, said sensor
including

15 sensor housing adapted for positioning in said gas flow, said sensor housing having a
longitudinal axis substantially perpendicular to said gas flow and a sensing end,

a locating tooth configured to mate with said depression notch, and

at least one projecting tab, extending laterally from said sensor housing, said at least one
projecting tab providing surfaces which enable liquid condensate to disperse away from said
20 sensing end of said sensor housing.

3. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 2 wherein said sensor comprises two projecting tabs.

4. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 2 or claim 3 wherein said two projecting tabs are oppositely positioned around said sensor housing.

5. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 2 or claim 3 wherein each said projecting tab is aligned parallel to said gas flow.

6. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 2 or claim 3 wherein liquid condensate is dispersed along lines of intersection between said sensor housing and each said tab, there existing a localised area of low surface tension along said lines of intersection.

7. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 2 or claim 3 wherein said sensor comprises a temperature sensor housing and a flow rate sensor housing.

8. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 7 wherein said temperature sensor housing and said flow rate sensor housing each comprise a temperature dependent resistance.

9. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 8 wherein temperature dependent resistance is occasionally heated to a predetermined difference temperature above the temperature of said gas flow, and the power required to maintain said predetermined difference temperature providing an indication of the flow rate of said gas.

10. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 7 wherein said flow rate sensor housing is exposed at or near the sensing end while said temperature sensor housing is encapsulated at or near the sensing end of the temperature sensor housing.

11. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 9 wherein said temperature and flow rate sensor housing are spaced across said gas flow in order that heat produced from said flow rate sensor housing has substantially minimal effect on said temperature sensor housing.

12. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 11 wherein said flow rate sensor housing is positioned downstream of said temperature sensor housing in order that heat produced by said flow rate sensor housing does not ~~effect~~ affect said temperature sensor housing.

13. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 2 or claim 3 wherein said gas flow is channeled within a conduit of known cross-sectional area, at least in the region adjacent said sensor, and is provided with said sensor entry port adapted to receive said sensor, the positioning of said temperature and flow rate sensor housing relative to said gas flow being controlled by the interconnection of said locating depression notch and tooth.

14. (Currently Amended) A breathing circuit component or conduit connector having an interior for conveying respiratory gas comprising:

a gas inlet communicating with said interior and configured to connect to an outlet of humidifier or other breathing assistance apparatus,
a gas outlet communicating with said interior and configured to connect to a conduit,
a sensor entry port configured to receive a sensor, and
a locating depression notch configured to receive a complementary locating tooth from a sensor, the interconnection of said depression notch and a tooth providing a predetermined orientation of a sensor within said interior.

15. (Currently Amended) A breathing circuit component as claimed in claim 14 wherein said sensor entry port comprises an annular cylinder extending perpendicularly from said conduit connector and having a passage communicating with and extending from said interior, said passage being substantially perpendicular to said interior.

16. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 15 wherein said locating ~~depression comprises a notch~~ is at an in the end of said cylinder distant said interior.

5 17. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 16 wherein said notch is substantially "V" shaped.

18. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 17 wherein a base of said "V" shaped notch is rounded.

10

19. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 18 wherein a diameter of said passage ensures a substantially airtight seal against a sensor located therein.

15 20. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 19 wherein said inlet includes an exterior surface comprising a tapered male portion configured to connect to a tapered female portion of an inner surface of an outlet of humidifier, or other breathing assistance apparatus.

20 21. (Currently Amended) A breathing circuit conduit connector component as claimed in claim 20 wherein said gas outlet includes an inner surface configured to form a substantially airtight seal against an exterior surface of a conduit.